

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
24 February 2005 (24.02.2005)

PCT

(10) International Publication Number
WO 2005/017581 A2

(51) International Patent Classification⁷: **G02B 6/00**

(21) International Application Number:
PCT/IB2004/051456

(22) International Filing Date: 13 August 2004 (13.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PCT/IB03/03682 15 August 2003 (15.08.2003) IB

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **TSUDA, Akimitsu**
[JP/JP]; c/o Philips Japan, Ltd., Philips Bldg., 2-13-37,
Kohnan, Minato-ku, Tokyo 108-8507 (JP).

(74) Agents: **TSUGARU, Susumu et al.**; c/o Philips Japan,
Ltd., Philips Bldg., 2-13-37, Kohnan, Minato-ku, Tokyo
108-8507 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: BACKLIGHT DEVICE



(57) Abstract: An asymmetric prism sheet 15 has a plurality of projections 17 having prism shape on its surface. The projection 17 comprises a first inclined surface 17a having a relatively gentle slope (easy slope) and a second inclined surface 17b having a relatively steep slope (steep slope). A base angle 17d on the side of the second surface 17b is α° and a base angle 17c on the side of the first surface 17a is β° . In the case that the light enters into the asymmetric prism sheet 15, which has the above-mentioned structure, from the bottom surface 15a (light guide plate 11), the light is mainly emitted in the substantially vertical direction (a direction inclined by relatively small angle to the vertical direction) in the first inclined surface 17a (arrows X), and is mainly emitted in the inclined direction (a direction inclined by relatively large angle to the vertical direction) in the second inclined surface 17b (arrows Y).



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.